



9.0L WATER BASED POLYMER SOLAR PANEL BLOCK-OUT INTERNAL CARTRIDGE CANISTER



SPECIFICATIONS

PART NUMBER	UKPVSTOP9-C
AGENT CAPACITY	9.0 LITRES
AGENT TYPE	PVSTOP (WATER BASED POLYMER)
TOTAL MASS	12.6KG
APPROVALS	EN3-8 AND PED 2014/68/EU
NOZZLE SIZE	3.2MM
DISCHARGE TIME	48 SECONDS
EFFECTIVE RANGE	10 METRES
DIMENSIONS	W179.5 X H575MM
CYLINDER PRESSURE TEST	5 YEARLY
PERIODIC TEST PRESSURE	27 BAR
CYLINDER CONSTRUCTION	STAINLESS STEEL
VALVE STEM	BRASS
CYLINDER FINISH	POLISHED STAINLESS STEEL
HANDLE FINISH	STAINLESS STEEL
VALVE FINISH	NICKEL PLATED BRASS



PVSTOP

2-(2-BUTOXYETHOXY)ETHANOL 1-10%, NITROGEN <=89%

**SOLAR PANEL
BLOCK OUT**

9.0L WATER BASED POLYMER

HAZARDOUS GOODS CLASS: 2.2
COMPRESSED GAS, N.O.S. (CONTAINS NITROGEN)
UN NUMBER: 3538
HAZCHEM CODE: 2TE
ADDITIONAL INFORMATION IS LISTED IN THE SAFETY DATA SHEET.

**INTERNAL CARTRIDGE
OPERATED**

PVSTOP INTERNATIONAL PTY LTD
6 / 276-278 NEW LINE ROAD, DURAL NSW 2158, AUSTRALIA
PHONE: +61 (0) 2 9652 5000
EMERGENCY: +44 (0) 1536 408409 (9-5PM)
WWW.PVSTOP.COM.AU